



MINI SDS

Equus Traxx 2000 HS Wearcoat Unit A

INGREDIENTS	CAS NO	%	8HR OEL
propylene glycol monomethyl ether acetate, alpha-isomer	108-65-6	10-20	274 mg/m3
xylene	1330-20-7	10-20	350 mg/m3
n-butyl acetate	123-86-4	1-10	713 mg/m3
naphtha petroleum, light aromatic solvent	64742-95-6.	1-10	-

GHS	DG
	 <p>UN No: 1263 Hazchem Code: *3Y DG Class: 3 Subsidiary Hazard: Not Applicable Packing Group: III Poisons Schedule: Not Applicable</p>

HEALTH HAZARD INFORMATION



Signal word:	Danger
Hazard statement(s):	H226 Flammable liquid and vapour.
	H304 May be fatal if swallowed and enters airways.
	H315 Causes skin irritation.
	H319 Causes serious eye irritation.
	H336 May cause drowsiness or dizziness.
	H412 Harmful to aquatic life with long lasting effects.
AUH019 May form explosive peroxides.	

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.PE/EVAL/PE 2.PVA 3.TEFLON
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs. Handle and open container with care.
Fire/Explosion Hazard:	Flammable. Toxic smoke/fumes in a fire.
Environment:	May cause long-term adverse effects in the aquatic environment.

PROPERTIES



Liquid. Does not mix with water. Sinks in water. Flammable. May form explosive peroxides.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water.
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



x — Must not be stored together

0 — May be stored together with specific preventions

+ — May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.