

CHEVAPRIME UM

Corrosion and stain resistant primer

February 2024

PURPOSE AND AREAS OF USE:

A corrosion and stain resistant primer for use on exterior and interior cementitious surfaces.

PRODUCT:

A waterborne modified acrylic primer, with special pigmentation to enhance stain-block and anti-rust capabilities.

PROCESS COMPATIBILITY:

Can be used as a primer under Chevaline waterborne acrylic coatings. May also be used under some Keim mineral paints (discuss with local Equus Respresentative).

STANDARD PACKS:

4, 10 and 20 litre plastic pails.

PHYSICAL PROPERTIES:

Liquid Material		Applied Film	
Solids (% by volume)	37%	Flexibility	Passes 2 mm mandrel
Specific Gravity	1.23	Adhesion	Excellent adhesion to the surfaces listed in Areas of Use.
Flash Point	Not applicable - waterborne material	Funnua Desistence	
Shelf Life	Three years in original sealed containers when stored in cool dry conditions and protected from frosts.	Fungus Resistance	Chevaprime UM contains a highly effective mould-resistant additive which does not contain toxic metals or phenols.

SURFACE PREPARATION:

Ensure surface to be coated is free of dust and contamination. Any form release agents and curing compounds, or remnants thereof, must be removed.

APPLICATION METHOD:

By brush, roller or spray direct from pail. Thinning is not normally required.

APPLICATION PROPERTIES:

Spreading Rate:

Theoretical	10-12 sqm/litre
Practical	8-10 sqm/litre
Recommended film thickness	35 µm

Dry times:

Touch dry	1-2 hours
Recoat time	6-8 hours

Thinning/Cleanup: Water

HEALTH AND SAFETY:

As a minimum protection wear protective clothing and barrier cream on hands when handling this product. It is a waterborne material and therefore, is non-flammable. However it is recommended NOT TO SMOKE when handling or applying this product. No special conditions are required other than protection from frost and prolonged heat. Refer to Safety Data Sheet before use.





CHEVAPRIME UM

Corrosion and stain resistant primer

WARNINGS AND BANS:

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?	No	
--	----	--

MANUFACTURERS CONTACT DETAILS:

Manufacture location	New Zealand
Legal and trading name of manufacturer	Equus Industries Ltd.
Manufacturer address for service	4 Sheffield Street, Blenheim 7274
Manufacturer website	www.equus.nz
Manufacturer email	info@equus.nz
Manufacturer phone number	03 578 0214
Manufacturer NZBN	9429032000306

The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations at any time without notice.



February 2024