

Chevaprime PBT

Purpose & Areas Of Use:

A general purpose primer for gypsum plaster, gibraltar board, hardboard, wood, wood composite boards and old enamel surfaces. Specially modified for wide surface compatibility.

Product:

A fast dry solvent borne modified alkyd primer.

Product Compatibility:

Use as a primer for:

Coverall	Covercryl	Arcutexx
Colourglaze	Extracover	Covertexx

Colours:

Off-white, light grey. Can be tinted to order but minimum quantity restrictions apply.

Standard Pack:

4 and 20 litre can.

Physical Properties:

Liquid Material:

Solids Volume:	34.7%
Specific Gravity:	1.18
Flash Point:	30°C
Shelf Life:	2 years in original sealed containers. Store in cool dry conditions and protect from frost.

Applied Material:

Flexibility:	Passes 2mm mandrel
Adhesion:	Excellent adhesion to the surfaces listed in "Areas Of Use" except on timbers such as Totara and Matai.
Fungus Resistance:	Chevaprime PBT contains a highly effective mould resistant additive which does not contain toxic metals or phenols.

Surface Preparation:

Ensure all surfaces to be coated are clean, dry, free of grease or oil contamination. Sand all board stopping smooth and sweep clean before priming and lightly sand old enamel surfaces and wipe with Xylol or mineral turps to remove residues. Remove all loose or flaking paint.

Application Method:

Apply by brush, roller or spray. If necessary thin sparingly with Xylol. **PBT Primer** should be stirred thoroughly before use.

Application Properties:

Spreading rate:

Theoretical	10-12 sqm/litre
Practical	10-15 sqm/litre

Recommended Film Thickness: 25-30µ

Dry time:

Touch dry	3-4 hours
Recoat time	16-24 hours

Clean up: Xylol

Health And Safety:

This primer contains solvent, and normal precaution should be applied, including the use of a cartridge mask when spraying or brushing in a confined space, barrier cream and/or gloves, and strict observation of a smoking ban in the operating area.

Shipping Information:

N.Z. Dangerous Goods Class:	3B
I.M.C.O Class:	3.3
U.N Number:	1263

Special Air Freight packaging regulations are applicable.

Equus Industries Ltd
PO Box 601
Blenheim
Phone: 03 578 0214
Email: admin@equus.nz
Web: www.equus.nz