

EQUUS LO SHEEN

Interior low sheen/silk paint

February 2024

PURPOSE AND AREAS OF USE:

An interior, low sheen/silk paint for use on most interior surfaces. Produces a smooth, tough, washable, burnish resistant finish.

PRODUCT:

A 100% acrylic, water based finish pigmented with titanium dioxide and inert extenders. It is a low odour product formulated for application at temperatures as low as 3°C.

PROCESS COMPATIBILITY:

Use with Equus Gib Sealer, Chevaprime PBT and Chevaprime U depending upon surface to be coated.

COLOUR:

Available in most BS5252 and BS2660 colours. Special colour matching is available, but may be subject to minimum batch quantities. Some very bright or strong colours may incur a colour surcharge.

STANDARD PACK:

5 and 15 litre plastic pails.

PHYSICAL PROPERTIES:

Liquid Material

Solids (% by volume)	37.2
Solids (% by weight)	55.6
Specific Gravity	1.42
Flash Point	None - waterborne material
Shelf Life	3 years in original sealed containers. Store in cool, dry conditions and protect from frost.

Applied Film

Durability	Excellent
Adhesion	Excellent to recommended primers, sealers and most previously painted surfaces.
Abrasion Resistance	Very good

SURFACE PREPARATION:

All surfaces to be coated must be cleaned to remove dirt, dust and any loose material. Ensure that the surfaces are also free of oil, grease or mould.

PRIMERS:

For gib board	Equus Gib Sealer
For timber, fibrous plaster, hardboard, particle board, fibre board	Chevaline PBT

APPLICATION PROPERTIES:

By brush, speed brush, roller or conventional/airless spray.

Spreading rate	10 sqm/litre
No. of coats	Normally 2 coats
Dry film thickness/coat	37 microns
Dry time - Touch dry	1 hour
Recoat time	2-4 hours
Dry times at 21°C and 50% relative humidity.	

EQUUS LO SHEEN

Interior low sheen/silk paint

February 2024

APPLICATION CONDITIONS:

Do not apply at temperatures below 3°C or when temperatures are liable to fall below this while drying.

HEALTH AND SAFETY:

Equus Lo Sheen is a waterborne material with Low VOC, is non flammable and contains no mammalian-toxic substances.

It requires no special storage conditions other than protection from excessive heat and frost. We recommend the use of barrier cream on exposed skin when handling this material.

WARNINGS AND BANS:

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?	No
--	----

MANUFACTURERS CONTACT DETAILS:

Manufacture location	New Zealand
Legal and trading name of manufacturer	Equus Industries Ltd.
Manufacturer address for service	4 Sheffield Street, Blenheim 7274
Manufacturer website	www.equus.nz
Manufacturer email	info@equus.nz
Manufacturer phone number	03 578 0214
Manufacturer NZBN	9429032000306