

Keim Concretal Dilution

Product Information:

Dilution for the special concrete protection coatings **Keim Concretal** and **Keim Concretal Lasur** reacts chemically with the surface. The product comprises of liquid special potassium silicate, pure acrylate, stabilisers.

Field Of Application:

Keim Concretal Dilution reacts chemically with the surface to which it is applied. Only to be used with **Keim Concretal** and **Keim Concretal Lasur** colourwash system.

Product Characteristics:

- Water vapour permeable
- Consolidates the surface
- Odourless
- Non toxic

Material Data:

Density: Q=1.047 g/cm³

Application:

Surface Preparation:

All loose and flaking paint should be removed using wire brushes and broad bladed scrapers to get back to a sound edge. When all surfaces are clean, sound, wind dry, dust free and free from all surface contaminants, decoration using **Keim Mineral Paints** may proceed.

Decoration:

Keim Concretal Grob should be diluted with 30% by weight **Keim Concretal Dilution** and applied by brush and roller, working well into all surfaces. After a minimum period of 12 hours a final coat of **Keim Concretal** in the chosen colour may be applied undiluted.

Air surface temperature >5°C

Tools:

Clean immediately after use with water.

Packaging:

5 & 25kg containers.

Storage:

Approximately 12 months, if kept cool, but frost free in tightly closed containers.

Identification Ref Ordinance Of Dangerous materials:

Not applicable.

Danger Class In Goods Traffic:

Not applicable

Safety Instructions:

Cover surfaces which are not to be painted, in particular glass, natural stone, ceramics etc. Protect the eyes and skin from splashes. Keep out of reach of children.

Refer to COSHH data sheet.

Equus Industries Ltd
PO Box 601
Blenheim
Phone: 03 578 0214
Email: admin@equus.nz
Web: www.equus.nz