



284

1 page

PRODUCT
DATA
SHEET

Keim Ecosil® Grund

Product Information:

Keim Ecosil Grund is a silicate based primer paint for interior.

Field Of Application:

Keim Ecosil Grund is a base coat to equalise different absorbencies and structures with repaired or filled surfaces as well as a base coat on plasterboard and adhering old coats of paint.

Product Characteristics:

- Equalises surfaces
- Levels structures
- Good adhesion

Material Data:

Specific Gravity: appr. 1.37 g/cm³
Resistance to vapour diffusion sd=0.03m
Degree of glossiness: matt

Colour Shades:

White

Packaging:

15 litre and 5 litre drums

Application:

Substrate Preparation:

Highly absorbing or sandy substrates should be treated with Keim Spezialfixativ.

Processing:

Keim Ecosil Grund has to be applied by brush or roller undiluted. A waiting period for the final coat with Keim Ecosil of at least 5 hours should be allowed, depending on the drying progress. Air and surface temperature >5°C.

Consumption:

Approx. 0.2 ltr/m² Keim Ecosil (for one coat).

Tools:

Clean immediately after use with water.

Storage:

Approx 12 months, cool but frost free in tightly closed drums.

Identification Ref Ordinance of Dangerous Material

Not applicable

Dangerous Class in Goods Traffic

Not applicable

Product Code

M-SK 10

Safety Instructions:

Cover surfaces which are not to be painted, in particular glass, natural stone, ceramic etc. Protect eyes and skin against splashes. Keep out of reach of children.

Equus Industries Ltd
PO Box 601
Blenheim
Phone: 03 578 0214 Fax 03 578 0919
Email: admin@equus.co.nz