

FLAGON TPO Walkway Supergrip

Description:

This protective layer is manufactured and approved by SOPREMA srl and can be used in combination with Flagon TPO membranes to easily create maintenance paths.

Use:

Protective sheet for walkways on roofs in combination with FLAGON TPO/FPO roofing membranes.

Application:

The FLAGON TPO Walkway Supergrip membranes are rolled out above the finished TPO waterproofing membrane as required and welded homogeneously to the top of the existing TPO roof waterproofing membrane using a hot air welding process in accordance with the laying guidelines. In order to avoid the formation of condensation between 2 closed sealing layers, only the upper weld to the roof membrane should be completely closed. The lower seam, on the other hand, should only be spot welded in order to ensure the security of the FLAGON TPO Walkway Supergrip. FLAGON TPO Walkway Supergrip sheets do not serve as sealing sheets but only as a protective layer and therefore do not have to be completely welded.

Technical Properties:

- Resistant to weather conditions and UV rays
- Flexible at low temperatures
- Heat resistant
- Optimal weldability
- 4mm membrane thickness
- Fire class E according to DIN EN 13501
- Slip class R 10 according to DIN 51130
- Embossed fishbone pattern

Storage & Transport:

The membrane must be stored horizontally on a level surface. Protect from direct sunlight, heat and moisture (rain, snow, etc.) for the duration of storage. During the cold season, the material must be stored at $>+5^{\circ}\text{C}$ for at least 12 hours before processing.



System Components:

- FLAGON TPO membrane range
- FLAGON EP/S homogeneous detailing membrane
- Molded parts (corners, pipe and lighting protection surrounds)
- FLAGON TPO Cleaner
- FLEXOCOL A 89 contact adhesive

Markings:

Roofing membrane according to EN 13956 DIN Spec 20000-201 Fire exposure according to EN 13501-1 Klasse E.
UNI EN ISO 9001 and UNI EN ISO 14001 certified number WPK 1085-CPD-0011.

Equus Industries Ltd
PO Box 601
Blenheim
Phone: 03 578 0214 Fax 03 578 0919
Email: admin@equus.co.nz
Website: www.equus.co.nz

© Equus Industries Ltd
Edition 2
August 2021