

FLEXOCOL A89

Adhesive for fleece-backed TPO membranes

March 2024

DESCRIPTION:

Mono-component adhesive formulated with polyurethane, liquid with medium-low viscosity, moisture-curing, with controlled expansion.

AREAS OF USE:

The adhesive FLEXOCOL A89 is used for bonding of membranes FLAGON TPO or FLAGON PVC coupled to geotextile on horizontal surfaces.

PACKAGING:

12 kg can.

APPLICATION:

- The supports must be clean and without inconsistent elements on the surface.
- The adhesive FLEXOCOL A89 can be spread and levelled using a brush, squeegee or roller.
- The adhesive must be applied on the whole support surface creating a thin and uniform layer.
- On dry supports, it is important to proceed by wetting using sprayed water.
- After 5-15 minutes from the application (according to the related environmental and support humidity), when the glue starts its reaction of foaming becoming white, it is possible to proceed by laying the membrane.
- First curing is after 2-4 hours while maximum adhesion level is normally obtained within 24-48 hours.
- Do not dilute the adhesive FLEXOCOL A89 with solvent or diluent.
- The laying tools can be cleaned with solvents or methyl ethyl ketone. Do not use any solvents containing alcoholic groups.

CONSUMPTION:

Minimum consumption is of about 300 to 400 g/m² on smooth and not very porous surfaces and can also be increased on porous and rough surfaces. The quantities are always purely indicative and should be evaluated considering the situation that may be encountered on the job-site.

TECHNICAL DATA:

Properties	FLEXOCOL A89
Specific weight at 20 (g/cm ³)	1.12 ± 5%
Water solubility:	Insoluble
Consistency	Viscose liquid
Minimal ambient application temperature (°C)	+ 5

STORAGE:

Shelf life	The shelf life is at least 10 months from production date printed on the packaging, provided that the same is stored in a dry place and in the original sealed and undamaged container.
Storage conditions	Store in a dry place at temperatures between +10°C and +30°C.



FLEXOCOL A89

Adhesive for fleece-backed TPO membranes

March 2024

STATEMENT OF RESPONSIBILITY:

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, their representative or the contractor is responsible for checking the suitability of products for their intended use.

Note: Field service where provided, does not constitute supervisory responsibility. Suggestions made by SOPREMA Australia Pty Ltd either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not SOPREMA Australia Pty Ltd are responsible for carrying out procedures appropriate to a specific application.

WARNINGS AND BANS:

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?	No
--	----

MANUFACTURERS CONTACT DETAILS:

Manufacture location	Italy
Legal and trading name of manufacturer	Soprema New Zealand Limited
Manufacturer address for service	Level 3, Candida Building 4, 61 Constellation Drive, Mairangi Bay, Auckland 0630, New Zealand
Manufacturer website	www.soprema.com.au
Manufacturer email	info@soprema.com.au
Manufacturer phone number	+61 3 9221 6230
Manufacturer NZBN	9429050312962