



Page 1 of 1

FLAGON SOLVENT 13

Solvent-based cleaning fluid

March 2024

DESCRIPTION:

FLAGON Solvent 13 is a solvent-based cleaning fluid used to prepare FLAGON TPO membranes during installation.

PACKAGING:

5 Litre Can.

TECHNICAL DATA:

Properties	FLAGON SOLVENT 13
Composition	Solvents
Application temperature	+5/+25°C

APPLICATION:

Use a solvent-proof and lint-free cloth. Where required, apply liberally to remove contaminants from the FLAGON TPO waterproofing membrane. Wait for the surface to dry and the solvents evaporate prior to welding.

STORAGE:

12 months in original unopened packaging, stored in a dry and cool place at a temperature between +5 and +25°C.

WARNINGS AND BANS:

MANUFACTURERS CONTACT DETAILS:

Manufacture location	Italy
Legal and trading name of manufacturer	Soprema New Zealand Limited
Manufacturer address for service	Level 3, Candida Building 4, 61 Constellation Drive, Mairangi Bay, Auckland 0630, New Zealand
Manufacturer website	www.soprema.com.au
Manufacturer email	info@soprema.com.au
Manufacturer phone number	+61 3 9221 6230
Manufacturer NZBN	9429050312962

The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations at any time without notice.