

SOPRASPRAY

Primer in a spray can

Description:

SOPRASPRAY is a ready-to-use fast-drying primer composed of bitumen and solvents. It provides excellent adhesion on existing bituminous membranes, metals, insulation boards, wood, concrete, brick and hard PVC. Application on insulation boards, wood, concrete, brick and hard PVC. Application on insulation boards based on styrene should be avoided.

Properties:

Composition:	bituminous and solvents
Consumption:	2 - 3.5 m ² / canister
Application temperature:	+10 / +35 °C
Curing time:	± 30 Min. (20 °C)

Packing & Storage:

Canister 500 ml

Minimum 12 months in original unopened packaging, stored in a dry and cool place at a temperature between +5 and +25 °C.

Installation:

Apply in a well-ventilated area. Shake the canister for 2 minutes before use. The surface must be clean, solid and free of dust and grease. Spray a uniform coat at a distance of about 30 cm away from the application area. After use, place the canister upside-down and purge the valve for a few seconds to avoid clogging.

Cleaning tools: White Spirit.

Special Indications:

Hygiene, Health and Environment

For more information, please refer to the relevant safety data sheet.

Quality, Environment and Safety Management

SOPREMA always recognises as a high level of importance, the quality of the products, the environment and safety. For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with EN ISO 9001 and EN ISO 14001

Equus Industries Ltd
PO Box 601
Blenheim
Phone: 03 578 0214
Email: admin@equus.nz
Website: www.equus.nz
August 2021