

AQUADERE

Water based primer

Description:

Cold applied solvent-free primer based on bitumen in aqueous phase. Impregnation to ensure good adhesion to the substrate (concrete, metal and wood) before welding (torch-on or hot-air method) or gluing bituminous waterproofing membranes. It is also suitable on old/weathered bituminous waterproofing membranes with a slate or granulate finish.

Properties:

Composition:	bitumen in aqueous phase
Curing time:	5 min. - 3 hrs.
Consumption (l/m ²):	0.20 - 0.35
Application temperature:	min +5

Packing & Storage:

Cans of 5 and 25 l.

12 months in original unopened packaging. Store frost-free and protected from sunlight at a temperature between +5 and +35°C.

Installation:

Thoroughly mix the product before use. Apply with a brush, roller or rubber squeegee on a dry, dust and grease free substrate. Allow to dry completely before applying the membrane. The tools must be free of dirt and residues of solvents as they might break the emulsion. See label for more information.

Cleaning tools:

- wet product - water
- dry product - White Spirit.

Certifications:



Special Indications:

Hygiene, Health and Environment

For more information, please refer to the relevant safety data sheet.

Quality, Environment and Safety Management

SOPREMA always recognises as a high level of importance, the quality of the products, the environment and safety. For this reason, we operate independently monitored Quality and Environment Assurance Systems in line with EN ISO 9001 and EN ISO 14001

Equus Industries Ltd
PO Box 601
Blenheim
Phone: 03 578 0214
Email: admin@equus.nz
Website: www.equus.nz
January 2024