

MONOPUR PIGMENT

Coloured resin paste

April 2024

PRODUCT:

- Monopur Pigment is a one-component coloured resin paste
- Available in a wide range of attractive colours
- Versatile packaging options for ease of use on site
- High colour density, high strength pigments provide excellent opacity

USES:

Used as pigment to colour the Monopur SL System range of products.

PACKAGING:

The product is supplied in full units as Pigment packs.

Component	
Pigment	0.2 kg
Pigment	1.2 kg
Pigment	10 kg
Pigment	20 kg

TECHNICAL DATA:

Standard Addition Rates	
Monopur SL (18 kg pack)	0.2 kg per 17.82 kg pack
Monopur SL (107 kg pack)	1.2 kg per 106.92 kg pack
Monopur Topcoat Satin	0.2 kg per 4.91 kg pack

COLOUR:

Please refer to the Monopur SL System TDS. Please ensure one batch is used to ensure colour consistency.

MIXING:

The product is supplied in full units as a single component. Pack components are pre-weighed for optimum performance.

Gently premix the pigment. Open packaging and pour pigment into mixing vessel as directed by the appropriate Monopur Technical Data Sheet (TDS). Ensure all contents of packaging have been removed.

Please refer to the appropriate Monopur Technical Data Sheet (TDS) as per required specification.

SOLVENT:

Solvent (Xylene / MEK / Acetone) should not be added to this product.

APPLICATION METHOD:

Please refer to the appropriate Monopur Technical Data Sheet (TDS) as per required specification.

MONOPUR PIGMENT

Coloured resin paste

April 2024

ADDITIONAL NOTES:

1. Please refer to the appropriate product Technical Data Sheet. The Technical Data Sheet, System Data Sheet and Safety Data Sheet must be read in conjunction with one another.
2. Maximum overcoat time is 24 hours at 20°C
3. The product has reached full chemical cure after 7 days at 20°C.
4. The applied colours may differ from the examples shown.
5. Light and vibrant colours may require additional coats to achieve desired results.
6. Equus Industries Ltd. assumes no responsibility for the application of incorrect colour.
7. It is the applicators responsibility to verify the accuracy of colour prior to application. Equus Industries Ltd. does not bear any responsibility or accept claims for incorrect colour after application of material.
8. It is recommended that top coat colours match base coat colours to achieve desired results.
9. The system is not UV stable and will discolour unless otherwise stated.
10. The system should have no contact with water for 5 days at 20°C or blooming may occur.
11. This system should be installed at 3°C above the dew point.
12. A low temperature/high humidity environment can cause blooming issues.
13. Please ensure application temperature and RH limits are followed.
14. Wind or strong airflow may cause quick curing and drying of the system.
15. Ensure wind or strong airflow is eliminated during application, however adequate ventilation should still be followed.
16. Direct heat during application of the system can cause flash curing and potential delamination.
17. Ensure you do not apply this system to substrates with temperatures exceeding 35°C.
18. The specific slip test rating (P0-P5 range) noted in this document is based on the system design, products listed, coverage rates and specific aggregate outlined in this document. This slip test rating can and will change if the standard specification details or installation methods are altered in any way. The specific slip rating (P0-P5 range) noted in this document is based on 96 Rubber slide testing on level non-inclined surfaces. Applications should refer to methods outlined in AS4586-2013 and SA HB 198:2014.

STORAGE:

Time	12 months in unopened packs. If longer than 12 months, contact Equus Industries Ltd.
Temperature	Storage temperature between 5°C and 35°C
Protection	Should be stored inside and protected from frost, weather, moisture, direct sunlight and contamination ingress.

HEALTH AND SAFETY:

Follow the appropriate Occupational Health and Safety guidelines applicable to the location where the application is undertaken. For more information, please refer to the Safety Datasheets (SDS) for the individual components.

WARNINGS AND BANS:

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?	No
--	----

MANUFACTURERS CONTACT DETAILS:

Manufacture location	Australia
Legal and trading name of manufacturer	Tremco CPG Pty Ltd.
Manufacturer address for service	12/4 Southridge Street, Eastern Creek, NSW 2766, Australia
Manufacturer website	
Manufacturer email	orders@tremco.com.au
Manufacturer phone number	+61 2 4648 0397