

# COLPHENE 3000

## Self-adhesive waterproofing membrane

February 2024

**DESCRIPTION:**

COLPHENE 3000 is a self-adhesive waterproofing membrane composed of SBS modified bitumen and a tri-laminated woven polyethylene facer. The underface is covered with silicone release film.

COLPHENE 3000 is designed for foundation walls and other below grade vertical surfaces, as well as a vapour barrier for warm and green roof systems.

This product can be used on most building surfaces, such as masonry, concrete and wood.

**PACKAGING:**

Specifications	COLPHENE 300
Thickness	1.5 mm
Dimensions	1 x 18.7 m
Weight	1.5 kg/m <sup>2</sup>
Selvage width	75 mm
Surface	Tri-laminated woven polyethylene
Underface	Silicone release film
Qty/Pallet	30

**TECHNICAL DATA:**

Properties	Standards	COLPHENE 3000
Tensile strength, MD/XD	ASTM D5147	11.3/15.4 kN/m
Tensile strength, MD/XD	ASTM D412	11.2/13.1 MPa
Ultimate elongation, MD/XD	ASTM D412	88/55 %
Ultimate elongation, MD/XD	ASTM D5147	40/25 %
Elongation of rubberised asphalt	ASTM D5147	> 1000 %
Flexibility at cold temperature	ASTM D5147	-35°C
Dynamic puncture	ASTM E154	747 N
Static puncture	ASTM D5602	400 N
Tear resistance, MD/XD	ASTM D5601	375/400 N
Lap adhesion	ASTM D1876	2000 N/m
Water absorption	ASTM D5147	0.1 % max
Peel resistance	ASTM D903	3500 N/m
Water vapour permeability	ASTM E96 (Procedure B)	< 2.5 ng/Pa·s·m <sup>2</sup> (< 0.04 perm) <small>All values are nominal</small>
Crack cycling at -32°C, 100 cycles	ASTM C836	Unaffected
Resistance to hydrostatic head	ASTM D5385	Minimum 114 m
Adhesion to strength to concrete -not primed -combined with primer	ASTM D1000	560 N/m 1650 N/m

(All values are nominal)



# COLPHENE 3000

## Self-adhesive waterproofing membrane

February 2024

**SCOPE OF USE:**

COLPHENE 3000 is used as waterproofing membrane for foundation walls and other below ground vertical surfaces (up to 3 m deep) with low risk of hydrostatic water pressure against concrete and masonry substrates. The membrane can be overlaid with an Equus approved drainage mat for protection.

COLPHENE 3000 can also be used as a vapour barrier in an Equus Soprema Warm Roof system where specified by the Condensation Risk Analysis (CRA). It is suitable for new builds and refurbishments, residential and commercial construction, in any location in New Zealand.

Suitable for other waterproofing applications with written approval by Equus Industries Ltd.

**SURFACE PREPARATION:**

The use of Equus Peel and Stick Primer for self-adhesive membranes is required before the installation of COLPHENE 3000 membrane.

The substrate should be clean, sound, dry and free of loose materials, grease and any contaminants, which may compromise the performance of the product.

**INSTALLATION:**

SELF-ADHESIVE COLPHENE 3000 membrane must be adhered to substrate by peeling off the silicone release film. Side lap joints must be a minimum of 75 mm and end lap joints must be a minimum of 150 mm. Once installed, pressure must be applied over the whole surface using a membrane roller to ensure good contact with the substrate. The upper most edge of the membrane shall be mechanically fastened using termination bars and sealed with a compatible SOPREMA sealant. Contact Equus for suitable sealant.

**Application temperatures:** Winter grade: -10 to 10°C, Summer grade: 10 to 50°C

**UV exposure:** up to 60 days

**RESTRICTION:**

Concrete must be cured a minimum of fourteen (14) days and an adhesion test is recommended before membrane application. For complete information on product installation, please consult your Equus Consultant.

**CONDITION OF USE:**

COLPHENE 3000 shall not be used on surfaces over 3 m below ground or in areas with high hydrostatic water pressure, in this case COLPHENE BSW waterproofing shall be used.

Written approval is required for this membrane to be used on a substrate or in a waterproofing system not outlined in the standard Equus specifications.

The product must be installed by a Certified Equus Applicator. Verification of their status can be confirmed by a current applicator certificate or by contacting Equus Industries Ltd. Any installation must be done in accordance with the latest specifications and technical documentation, or with written approval by Equus Industries Ltd.

**BUILDING CODE COMPLIANCE:**

**B2 Durability** - B2.3.1 (a,b), COLPHENE 3000 has a durability of at least 50 years where used underground and at least 15 years where used above ground, when installed with the correct specification, installation and maintenance. BRANZ Appraisal 1037.

**E2 External moisture** - E2.3.2, E2.3.3, E2.3.7 Test data, together with in-service history in New Zealand and internationally, of the correctly installed COLPHENE 3000 membrane over correctly designed and constructed substrates, show that the membrane successfully resists the ingress of moisture. See BRANZ Appraisal 1037.

**F2 Hazardous building materials** - F2.3.1 Well known experience with the type of materials used together with in-service history, show that COLPHENE 3000 complies with this performance requirement. Refer to SDS at [www.equus.nz](http://www.equus.nz)

# COLPHENE 3000

## Self-adhesive waterproofing membrane

February 2024

### SUPPORTING DOCUMENTATION:

Title (type)	Version	URL
BRANZ Appraisal No. 1037	22 April 2022	<a href="https://www.equus.nz/content/reports/branz-appraisal-colphene-1037.pdf">https://www.equus.nz/content/reports/branz-appraisal-colphene-1037.pdf</a>

### STORAGE AND HANDLING:

Rolls must be stored upright, with the selvedge side on top. If the product is stored outdoors, cover them with an opaque protective cover after removal of the delivery packaging.

### HEALTH AND SAFETY:

The product does not contain any substance which is likely to be detrimental to your health or the environment and complies with generally admitted Health and Safety Requirements. For more information, please refer to the relevant Safety Data Sheet.

### WARNINGS AND BANS:

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?	No
--------------------------------------------------------------------------------------------------------------------	----

### MANUFACTURERS CONTACT DETAILS:

Manufacture location	Canada
Legal and trading name of manufacturer	Soprema New Zealand Limited
Manufacturer address for service	Level 3, Candida Building 4, 61 Constellation Drive, Mairangi Bay, Auckland 0630, New Zealand
Manufacturer website	<a href="http://www.soprema.com.au">www.soprema.com.au</a>
Manufacturer email	<a href="mailto:info@soprema.com.au">info@soprema.com.au</a>
Manufacturer phone number	+61 3 9221 6230
Manufacturer NZBN	9429050312962