

FIX 10-S

Plugging Cement

Properties:

- Chloride free
- Highly reactive rapid setting cement
- Immediately starts to set upon addition of water
- For interior and exterior use.

Areas of Application:

Immediate waterproofing of water leaks, water penetration and seepage in cellars, shafts, tunnels etc.

Technical Data:

Basis:	cement, additives
Colour:	cement grey
Bulk weight	approx. 1.2kg/dm ³
Substrate, application temperature:	+5° C to +30° C
Start of setting:	immediately after water addition
Consumption:	approx. 2 kg per litre of void
Storage	dry, 12 months in the original unopened packaging. Use opened packaging promptly.
Packaging	6 and 12 kg plastic buckets

Surface preparation:

The substrate must be sound, load-bearing, clean and free from adhesion inhibiting materials. Remove loose render and masonry sections. To improve the anchoring of FIX 10-S, chop out the leaking area, as necessary, to form a swallow tail before plugging.

Product preparation:

Plugging of leaks can be achieved by pressing FIX 10-S, in the dry form, into the leaking area by hand. If the leaking area is not sealed by the first plugging attempt, FIX 10-S can be applied again followed by several coats of AQUAFIN-F, which is then included within the surface applied waterproof membrane selected.

Advice:

- Protect areas not being treated with FIX 10-S.
- Carry out appropriate preliminary tests.
- If the leakage area is large, we recommend the AQUAFIN-1F and AQUAFIN-1K system.
- Do not mix FIX 10-S with or bring into contact with gypsum.

Please observe a valid EU Health & Safety Data sheet.

GISCODE:ZP1

Equus Industries Ltd
PO Box 601
Blenheim
Phone: 03 578 0214
Email: admin@equus.nz
Web: www.equus.nz
October 2022