

# DUO ROOF & DECK MEMBRANE SYSTEM

## Two-layer bitumen membrane waterproofing

March 2024

### PURPOSE AND SCOPE OF USE:

The DUO Roof & Deck Membrane system is a torch-applied waterproofing system, consisting of two-layers of modified bitumen membrane forming a 6.5 mm thick layer. DUO provides a fire-retardant, UV-resistant, flexible waterproofing membrane designed for exposed flat roofs and decks, and other areas such as podiums, balconies and terraces.

The system has a range of base sheets and cap sheets suitable for different building requirements, including self-adhesive membranes, making it a customisable solution with UV and weather resistance suitable for any location and wind zone in New Zealand. With the correct primer, DUO can be applied over concrete, plywood and CLT substrates.

Suitable for new builds and refurbishments, residential and commercial construction.

DUO Roof & Deck Membrane can be overlaid with Fixplus or other approved pedestals, pavers and decking, Kraitec Step walkway tiles, or SOPRASOLAR non-penetrative solar panel supports or other approved supports.

Suitable for other waterproofing applications with written approval by Equus Industries Ltd.

### PRODUCTS:

The system encompasses a selection of the products below. Refer to standard specifications for full specification details. Technical datasheets and specifications can be found on <https://www.equus.nz>.

|                             |  |
|-----------------------------|--|
| SOPRADERE QUICK             | SOPRASTICK                             |
| EQUUS Peel and Stick Primer | SOPRASTICK VENTI TACK PLUS             |
| DEBOFLEX 2.5 T/F C175       | DUO HT 4 Slates/F C180 FC (or variant) |
| SOPRASUN PLUS 3             |  |

### SPECIFICATIONS:

|   |
|---|
| P3401 DUO on concrete substrate                             |
| P3402 DUO on plywood substrate                              |
| Masterspec 4421EB Equus DUO Roof & Deck Membrane by SOPREMA |

### COLOUR:

Standard Cap Sheet Colours: GW (Grey White), AGR (Black), WGG (White Grey Green), BO (Brown Oxide). Colour availability is stock dependant and may need to be specially ordered.

### CONDITIONS OF USE:

In areas of regular foot traffic, higher than for normal maintenance traffic, the membrane must be overlaid with Fixplus pedestals and pavers or decking, Kraitec Step walkway tiles or other approved protection.

The product must be installed by a Certified Equus Applicator. Verification of their status can be confirmed by a current applicator certificate or by contacting Equus Industries. Any installation must be done in accordance with the latest specifications and technical documentation, or with written approval by Equus Industries Ltd.

# DUO ROOF & DECK MEMBRANE SYSTEM

## Two-layer bitumen membrane waterproofing

**March 2024**
**BUILDING CODE COMPLIANCE:**

**B2 Durability** - B2.3.1 (b), DUO Roof & Deck Membrane has a durability of at least 15 years, and a life expectancy of 35 years, when installed with the correct specification, installation and maintenance. See CodeMark CMNZ70151, BRANZ Appraisal 685, DUO Durability Study.

**E2 External moisture** - E2.3.1, E2.3.2, E2.3.7 Test data, together with in-service history in New Zealand and internationally, of the correctly installed DUO Roof & Deck Membrane over correctly designed and constructed substrates, show that the membrane successfully resists the ingress of moisture. See BRANZ Appraisal 685, DUO Durability Study.

**F2 Hazardous building materials** - F2.3.1 Well known experience with the type of materials used together with in-service history, show that DUO Roof & Deck Membrane complies with this performance requirement. Refer to SDS at [www.equus.nz](http://www.equus.nz)

**SUPPORTING DOCUMENTATION:**

The following additional documentation supports the above statements:

| Title (type)  | Version       | URL   |
|---|---------------|---|
| Codemark Certificate CMNZ70151                                      | 30 June 2023  | <a href="https://equus.nz/content/reports/codemark-soprema-waterproofing-membranes.pdf">https://equus.nz/content/reports/codemark-soprema-waterproofing-membranes.pdf</a> |
| BRANZ Appraisal No. 685   | 27 April 2022 | <a href="https://www.equus.nz/content/reports/branz-appraisal-duo-685.pdf">https://www.equus.nz/content/reports/branz-appraisal-duo-685.pdf</a>                           |
| DUO Durability Study  | 2018          | <a href="https://www.equus.nz/content/reports/durability-study-duo.pdf">https://www.equus.nz/content/reports/durability-study-duo.pdf</a>                                 |
| Technical Datasheets for products listed on page 1 of this document |               | Technical datasheets can be found on <a href="https://equus.nz">https://equus.nz</a> .  |

**WARNINGS AND BANS:**

|  |    |
|--|----|
| Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004? | No |
|--|----|

**MANUFACTURER CONTACT DETAILS:**

|  |  |
|--|--|
| Manufacture location                   | New Zealand                                      |
| Legal and trading name of manufacturer | Equus Industries Ltd.                            |
| Manufacturer address for service       | 4 Sheffield Street, Blenheim 7274                |
| Manufacturer website                   | <a href="http://www.equus.nz">www.equus.nz</a>   |
| Manufacturer email                     | <a href="mailto:info@equus.nz">info@equus.nz</a> |
| Manufacturer phone number              | 03 578 0214                                      |
| Manufacturer NZBN                      | 9429032000306                                    |