



TROWELTEXX 2000 REMEDIAL SYSTEM

Trowel applied synthetic textured wall finish

December 2023

PURPOSE AND AREAS OF USE:

The Chevaline Troweltexx 2000 remedial system is a waterproof plaster system designed as a full crack repair and remedial system for building refurbishments in the residential or commercial industry.

The system offers an acrylic plaster and mesh combination that encapsulates the building with a waterproof and flexible layer and a textured finishing plaster. To achieve a long-life, low-maintenance, weatherproof finish the texture system is coated with Equus high build Chevaline coatings.

Chevaline Troweltexx 2000 is a highly filled, heavy body waterborne acrylic coating available in a series of aggregate grades.

- Troweltexx Standard (1mm aggregate)
- Troweltexx Medium (2mm aggregate)
- Troweltexx Coarse (3mm aggregate)

PRODUCT:

The system encompasses the products below. Specifications are engineered specifically to clients' requirements.

Suitable primer for substrate Thermexx Detail Plaster Thermexx Mesh Chevaline Troweltexx 2000 Chevaline Coverall Chevaline Stonewash Chevaline Colourglaze

COLOUR:

Custom colours are available to match any colour chart.

SCOPE OF USE:

The Troweltexx 2000 system can be used over tilt slab concrete, concrete block, plastered systems and other approved substrates including monolythic cladding systems. As a remedial system is can be applied over a number of existing finishes and plaster. Suitable primer and number of coats are dependent on the substrate and the end use of the building, this can be confirmed with a specific specification provided by Equus industries Ltd.

The Troweltexx 2000 system is suitable as an exterior coating for new builds or refurbishments in the residential or commercial sector. Troweltexx 2000 can be used in all areas across the country including coastal areas.

The system can be be applied in a wide range of applications where approved by Equus Industries Ltd.

CONDITIONS OF USE:

Chevaline Troweltexx 2000 remedial system can be used with substrates meeting the requirements laid out in the TDSs at www.equus.nz. The installation must be done by a Certified Equus Applicator. Verification of their status can be confirmed by a current applicator certificate or by contacting Equus Industries Ltd. Any installation must be done in accordance with the latest specifications and technical documentation, or with written approval by Equus Industries Ltd.

WARRANTY:

Chevaline Troweltexx 2000 may be warranted for a period of up to 15 years depending of specification, substrate and end use requirement.

The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations at any time without notice





TROWELTEXX 2000 REMEDIAL SYSTEM

Trowel applied synthetic textured wall finish

December 2023

BUILDING CODE COMPLIANCE:

B2 Durability - B2.3.1 (a), B2.3.2 (a,b) Chevaline Troweltexx 2000 Remedial System has a durability of at least 5 years when installed with the correct specification, installation, and maintenance. Re-coating specifications are available to extend the life of the membrane.

E2 External moisture - E2.3.2, E2.3.7 Chevaline Troweltexx 2000 Remedial System test data together with in-service history of the correctly installed over correctly designed and constructed substrates, show that the membrane resists the ingress of moisture.

F2 Hazardous building materials - F2.3.1 Well known experience with the type of materials used together with in-service history, show that Chevaline Troweltexx 2000 Remedial System complies with this performance requirement. Refer to SDS at www.equus.nz

SUPPORTING DOCUMENTATION:

The following additional documentation supports the statements on the previous page:

Title (type)	Version	URL
Technical Data Sheets listed on page 1 of this document		Technical datasheets can be found on https://equus.nz.

WARNINGS AND BANS:

MANUFACTURER CONTACT DETAILS:

Manufacture location	New Zealand
Legal and trading name of manufacturer	Equus Industries Ltd.
Manufacturer address for service	4 Sheffield Street, Blenheim 7274
Manufacturer website	www.equus.nz
Manufacturer email	info@equus.nz
Manufacturer phone number	03 578 0214
Manufacturer NZBN	9429032000306

The information in this product data sheet is based on our experience and testing. It represents the latest information available at the time of printing, but no guarantee of its accuracy is made or implied, nor responsibility taken for use to which this information may be put. We reserve the right to alter or up-date information parameters and formulations at any time without notice.